

SK	Gear Unit	Shaft/Mounting	Reducer Options	Motor/Input	Motor Options
	1	2	3	4	

Gear Unit			
0182NB	1382NB	1282/02	6382/22
0282NB	2382	2282/02	6382/32
1282	3382	3282/12	7382/22
2282	4382	4282/12	7382/32
3282	5382	5282/12	8382/22
4282	6382		8382/32
5282	7382		9382/42
6282	8382		9382/52
7282	9382		10382/52
8282	10382		11382/52
9282	11382		
10282	12382		
11282			

Shaft/Mounting		
<input type="checkbox"/> VZ - Solid Shaft/B14 Flange	<input type="checkbox"/> VX - Solid Shaft/Foot	<input type="checkbox"/> AZ - Hollow Shaft/B14 Flange
<input type="checkbox"/> VF - Solid Shaft/B5 Flange	<input type="checkbox"/> LX - Double Solid Shaft/Foot	<input type="checkbox"/> AF - Hollow Shaft/B5 Flange
<input type="checkbox"/> SCP - Screw Conveyor Package		<input type="checkbox"/> AX - Hollow Shaft/Foot

Reducer Options		
<input type="checkbox"/> B - Fixing Kit	<input type="checkbox"/> LL - Long Term Storage	<input type="checkbox"/> Cross Drilled Shaft
<input type="checkbox"/> G - Rubber Buffers	<input type="checkbox"/> VL - Heavy Duty Output Bearings	<input type="checkbox"/> FKM - Fluoro-rubber Seals
<input type="checkbox"/> VG - Heavy Duty Rubber Buffers	<input type="checkbox"/> VL2 - Spread Bearing Design	<input type="checkbox"/> OSG - Oil Sight Glass
<input type="checkbox"/> H - Hollow Shaft Cover	<input type="checkbox"/> VL3 - Oil Safe Spread Bearing Design	<input type="checkbox"/> OA - Oil Expansion Chamber
<input type="checkbox"/> H66 - IP66 Hollow Shaft Cover	<input type="checkbox"/> VL4 - Drywell Drop Bearing Design	<input type="checkbox"/> OC - Oil Cooler
<input type="checkbox"/> SH - Shrink Disc & Cover	<input type="checkbox"/> LX - Double Solid Shaft	<input type="checkbox"/> WC - Water Cooling Cover
<input type="checkbox"/> VSH - Heavy Duty Shrink Disc & Cover	<input type="checkbox"/> SM5 - Stainless Steel Output Shaft	<input type="checkbox"/> OT - Oil Reservoir Tank
<input type="checkbox"/> M - GRIPMAXX™	<input type="checkbox"/> SWA - Special Hollow Shaft	<input type="checkbox"/> MDP - Magnetic Drain Plug
<input type="checkbox"/> PR - Flange Pilot Removal	<input type="checkbox"/> SWV - Special Solid Shaft	<input type="checkbox"/> ADP - Additional Drain Plug

Input Shaft	NEMA Adapter	IEC	Integral Motors	Integral Premium Efficient Motors	Integral Intermittent Duty (60 min) Motors	Scoop	Motor Platform	Servo Adapter (Keyed)	
W	N56C	IEC 63	63S/4 - 0.16hp	80LP/4 - 1hp	225RP/4 - 40hp	80L/4 - 1hp	S56	MKN056	SEP 100
	N140TC	IEC 71	63L/4 - 0.25hp	90SP/4 - 1.5hp	225SP/4 - 50hp	90S/4 - 1.5hp	S140T	MKN140	SEP 130
	N180TC	IEC 80	71S/4 - 0.33hp	90LP/4 - 2hp	225MP/4 - 60hp	90L/4 - 2hp	S180T	MKN180	SEP 165
	N210TC	IEC 90	71L/4 - 0.50hp	100LP/4 - 3hp	250WP/4 - 75hp	100L/4 - 3hp	S210T	MKN210	SEP 215
	N250TC	IEC 100	80S/4 - 0.75hp	112MP/4 - 5hp	280SP/4 - 100hp	100LA/4 - 5hp	S250T	MKN250	SEP 300
	N280TC	IEC 112		132SP/4 - 7.5hp	280MP/4 - 125hp	112M/4 - 5.4hp	S280T	MKN280	Servo Adapter (Clamp)
	N320TC	IEC 132		132MP/4 - 10hp	315SP/4 - 150hp	132S/4 - 7.5hp	S320T	MKN320	
	N360TC	IEC 160		160MP/4 - 15hp	315MP/4 - 175hp	132M/4 - 10hp	S360T	MKN360	SEP 100
	N400TC	IEC 180		160LP/4 - 20hp	315RP/4 - 200hp	160M/4 - 15hp	S400T	MKN400	SEP 130
		IEC 200		180MP/4 - 25hp	315LP/4 - 250hp	160L/4 - 20hp			SEP 165
		IEC 225		180LP/4 - 30hp		180MX/4 - 25hp			SEP 215
		IEC 250				180LX/4 - 30hp			SEP 300
		IEC 280				200LX/4 - 40hp			
		IEC 315							

Product Specifications

Ratio

 :1

Mounting Position

- M1
- M2
- M3
- M4
- M5
- M6
- Special _____

Paint

- Standard Stainless Steel Paint
- NSD+ (gray)
- NSD+W (white)
- NSD-X3 (gray)
- NSD-X3W (white)
- Casting Primed
- Special _____

Lubricant

- Standard
- Synthetic
- Food Grade
- Other _____

Shaft Diameter (If required)


B5 Flange Diameter (If required)

SCP Drive Shaft Diameter (If required)

Gearmotor Only Details

- Voltage & Frequency**
- 230/460V-60Hz (460V only ≥ 40 hp)
 - 575V-60Hz
 - 208V-60Hz
 - 400V-50Hz
 - 115/230V-60Hz, 1 ph.
 - Other _____

- Terminal Box Pos.**
- TB1
 - TB2
 - TB3
 - TB4



- Conduit Entry Loc.**
- CE I*
 - CE II
 - CE III
 - CE IV*

