

# FLEXBLOC™ Ordering Guide



Gear Unit	FLEXBLOC™ Size	Reducer Options	Input Option	Motor	Motor Options																										
SK					see pages 222 - 233																										
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:50%;">FLEXBLOC™ Design</th> <th style="width:50%;">FLEXBLOC™ Size</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">1SI</td> <td> <input type="radio"/> 31  <input type="radio"/> 40  <input type="radio"/> 40/31  <input type="radio"/> 50  <input type="radio"/> 50/31  <input type="radio"/> 63  <input type="radio"/> 63/31  <input type="radio"/> 75  <input type="radio"/> 75/40                 </td> </tr> <tr> <td colspan="2" style="text-align: center;"><b>Shafts</b></td> </tr> <tr> <td colspan="2"> <input type="radio"/> Inch  <input type="radio"/> Metric                 </td> </tr> </tbody> </table>		FLEXBLOC™ Design	FLEXBLOC™ Size	1SI	<input type="radio"/> 31 <input type="radio"/> 40 <input type="radio"/> 40/31 <input type="radio"/> 50 <input type="radio"/> 50/31 <input type="radio"/> 63 <input type="radio"/> 63/31 <input type="radio"/> 75 <input type="radio"/> 75/40	<b>Shafts</b>		<input type="radio"/> Inch <input type="radio"/> Metric		<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">Reducer Options</th> </tr> </thead> <tbody> <tr> <td><input type="checkbox"/> <b>V</b> - Plug in Solid Output Shaft  30</td> <td><input type="radio"/> VA <input type="radio"/> VB <input type="radio"/> Unassembled</td> </tr> <tr> <td><input type="checkbox"/> <b>L</b> - Double Solid Shaft Extension  31</td> <td></td> </tr> <tr> <td><input type="checkbox"/> <b>F</b> - B5 Output Flange  31</td> <td><input type="radio"/> FA <input type="radio"/> FB <input type="radio"/> FF <input type="radio"/> Unassembled</td> </tr> <tr> <td><input type="checkbox"/> <b>D</b> - Torque Arm  31</td> <td><input type="radio"/> DA <input type="radio"/> DB <input type="radio"/> Unassembled</td> </tr> <tr> <td><input type="checkbox"/> <b>H</b> - Shaft Cover  30</td> <td><input type="radio"/> HA <input type="radio"/> HB <input type="radio"/> Unassembled</td> </tr> <tr> <td><input type="checkbox"/> <b>X</b> - Foot Plate  31</td> <td></td> </tr> <tr> <td><input type="checkbox"/> <b>J</b> - Shaft Bushing _____ size  31</td> <td></td> </tr> <tr> <td><input type="checkbox"/> <b>H10</b> - Helical Input Stage (10:1)  33</td> <td></td> </tr> </tbody> </table>	Reducer Options		<input type="checkbox"/> <b>V</b> - Plug in Solid Output Shaft  30	<input type="radio"/> VA <input type="radio"/> VB <input type="radio"/> Unassembled	<input type="checkbox"/> <b>L</b> - Double Solid Shaft Extension  31		<input type="checkbox"/> <b>F</b> - B5 Output Flange  31	<input type="radio"/> FA <input type="radio"/> FB <input type="radio"/> FF <input type="radio"/> Unassembled	<input type="checkbox"/> <b>D</b> - Torque Arm  31	<input type="radio"/> DA <input type="radio"/> DB <input type="radio"/> Unassembled	<input type="checkbox"/> <b>H</b> - Shaft Cover  30	<input type="radio"/> HA <input type="radio"/> HB <input type="radio"/> Unassembled	<input type="checkbox"/> <b>X</b> - Foot Plate  31		<input type="checkbox"/> <b>J</b> - Shaft Bushing _____ size  31		<input type="checkbox"/> <b>H10</b> - Helical Input Stage (10:1)  33				
FLEXBLOC™ Design	FLEXBLOC™ Size																														
1SI	<input type="radio"/> 31 <input type="radio"/> 40 <input type="radio"/> 40/31 <input type="radio"/> 50 <input type="radio"/> 50/31 <input type="radio"/> 63 <input type="radio"/> 63/31 <input type="radio"/> 75 <input type="radio"/> 75/40																														
<b>Shafts</b>																															
<input type="radio"/> Inch <input type="radio"/> Metric																															
Reducer Options																															
<input type="checkbox"/> <b>V</b> - Plug in Solid Output Shaft  30	<input type="radio"/> VA <input type="radio"/> VB <input type="radio"/> Unassembled																														
<input type="checkbox"/> <b>L</b> - Double Solid Shaft Extension  31																															
<input type="checkbox"/> <b>F</b> - B5 Output Flange  31	<input type="radio"/> FA <input type="radio"/> FB <input type="radio"/> FF <input type="radio"/> Unassembled																														
<input type="checkbox"/> <b>D</b> - Torque Arm  31	<input type="radio"/> DA <input type="radio"/> DB <input type="radio"/> Unassembled																														
<input type="checkbox"/> <b>H</b> - Shaft Cover  30	<input type="radio"/> HA <input type="radio"/> HB <input type="radio"/> Unassembled																														
<input type="checkbox"/> <b>X</b> - Foot Plate  31																															
<input type="checkbox"/> <b>J</b> - Shaft Bushing _____ size  31																															
<input type="checkbox"/> <b>H10</b> - Helical Input Stage (10:1)  33																															
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:20%;">Input Shaft</th> <th style="width:30%;">NEMA Adapter</th> <th style="width:50%;">IEC</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">W</td> <td style="text-align: center;">N48C N56C N140TC N180TC</td> <td style="text-align: center;">IEC 63 IEC 71 IEC 80 IEC 90 IEC 100 IEC 112</td> </tr> </tbody> </table>		Input Shaft	NEMA Adapter	IEC	W	N48C N56C N140TC N180TC	IEC 63 IEC 71 IEC 80 IEC 90 IEC 100 IEC 112	<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th style="width:50%;">Motors</th> <th style="width:50%;">Premium Efficient Motors</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">63S/4 - 0.16hp 63L/4 - 0.25hp 71S/4 - 0.33hp 71L/4 - 0.50hp 80S/4 - 0.75hp</td> <td style="text-align: center;">80LP/4 - 1hp 90SP/4 - 1.5hp 90LP/4 - 2hp 100LP/4 - 3hp 112MP/4 - 5hp</td> </tr> </tbody> </table>		Motors	Premium Efficient Motors	63S/4 - 0.16hp 63L/4 - 0.25hp 71S/4 - 0.33hp 71L/4 - 0.50hp 80S/4 - 0.75hp	80LP/4 - 1hp 90SP/4 - 1.5hp 90LP/4 - 2hp 100LP/4 - 3hp 112MP/4 - 5hp	Other Pole & Speed Options available																	
Input Shaft	NEMA Adapter	IEC																													
W	N48C N56C N140TC N180TC	IEC 63 IEC 71 IEC 80 IEC 90 IEC 100 IEC 112																													
Motors	Premium Efficient Motors																														
63S/4 - 0.16hp 63L/4 - 0.25hp 71S/4 - 0.33hp 71L/4 - 0.50hp 80S/4 - 0.75hp	80LP/4 - 1hp 90SP/4 - 1.5hp 90LP/4 - 2hp 100LP/4 - 3hp 112MP/4 - 5hp																														

## Product Specifications

Single Worm	Helical Worm (1SI_/H10)		Double Worm (1SI_/_)		Paint	Torque Arm Orientation (If Selected)						
Ratio	Ratio	Position	Ratio	Position								
<input type="radio"/> 5	<input type="radio"/> 50	<input type="radio"/> T1	<input type="radio"/> 150	<input type="radio"/> U1	<input type="radio"/> No Paint (Standard)							
<input type="radio"/> 7.5	<input type="radio"/> 75	<input type="radio"/> T2	<input type="radio"/> 225	<input type="radio"/> U2	<input type="radio"/> Stainless Steel Paint							
<input type="radio"/> 10	<input type="radio"/> 100	<input type="radio"/> T3	<input type="radio"/> 300	<input type="radio"/> U3	<input type="radio"/> NSD+ (gray)							
<input type="radio"/> 12.5	<input type="radio"/> 125	<input type="radio"/> T4	<input type="radio"/> 375	<input type="radio"/> U4	<input type="radio"/> NSD+W (white)							
<input type="radio"/> 15	<input type="radio"/> 150		<input type="radio"/> 450	<input type="radio"/> U5	<input type="radio"/> NSD-X3 (gray)							
<input type="radio"/> 20	<input type="radio"/> 200		<input type="radio"/> 600	<input type="radio"/> U6	<input type="radio"/> NSD-X3W (white)							
<input type="radio"/> 25	<input type="radio"/> 250		<input type="radio"/> 750	<input type="radio"/> U7	<input type="radio"/> NSD <sup>toph</sup>							
<input type="radio"/> 30	<input type="radio"/> 300		<input type="radio"/> 900	<input type="radio"/> U8	<input type="radio"/> Special _____							
<input type="radio"/> 40	<input type="radio"/> 400		<input type="radio"/> 1200									
<input type="radio"/> 50	<input type="radio"/> 500		<input type="radio"/> 1500									
<input type="radio"/> 60	<input type="radio"/> 600		<input type="radio"/> 1800									
<input type="radio"/> 80	<input type="radio"/> 800		<input type="radio"/> 2400									
<input type="radio"/> 100	<input type="radio"/> 1000		<input type="radio"/> 3000									
					<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2">Torque Arm Orientation (If Selected)</th> </tr> </thead> <tbody> <tr> <td><input type="radio"/> Side A</td> <td></td> </tr> <tr> <td><input type="radio"/> Side B</td> <td></td> </tr> </tbody> </table>		Torque Arm Orientation (If Selected)		<input type="radio"/> Side A		<input type="radio"/> Side B	
Torque Arm Orientation (If Selected)												
<input type="radio"/> Side A												
<input type="radio"/> Side B												

## Gearmotor Only Details

Voltage & Frequency
<input type="radio"/> 208V-60Hz
<input type="radio"/> 230/460V-60Hz
<input type="radio"/> 575V-60Hz
<input type="radio"/> 400V-50Hz
<input type="radio"/> Other _____

Terminal Box Position
<input type="radio"/> KK1
<input type="radio"/> KK2
<input type="radio"/> KK3
<input type="radio"/> KK4

Conduit Entry Location
<input type="radio"/> I *
<input type="radio"/> II
<input type="radio"/> III *
<input type="radio"/> IV

\* Brakemotor options