

2 Stage Bevel Ordering Guide



92.1 Bevel



93.1 Bevel



DRIVESYSTEMS

SK	① Gear Unit	② Shaft/Mounting	③ Shaft/Mounting Options	④ Reducer Options	⑤ Motor/Input	Motor Options
-----------	-------------	------------------	--------------------------	-------------------	---------------	---------------

① Gear Unit	
92072.1	93072.1
92172.1	93172.1
92372.1	93372.1
92672.1	93672.1
92772.1	93772.1

② 92.1 Shaft/Mounting	
<input type="checkbox"/> V - Universal Feet/B14 Face Flange/Solid Shaft	<input type="checkbox"/> A - Universal Feet/B14 Face Flange/ Hollow Shaft
<input type="checkbox"/> VF - Universal Feet/B5 Flange/Solid Shaft	<input type="checkbox"/> AF - Universal Feet/B5 Flange/ Hollow Shaft
<input type="checkbox"/> L - Universal Feet/B14 Face Flange/Double Solid Shaft	

② 93.1 Shaft/Mounting	
<input type="checkbox"/> V - B14 Face Flange/Solid Shaft	<input type="checkbox"/> A - B14 Face Flange/Hollow Shaft
<input type="checkbox"/> VF - B5 Flange/ Solid Shaft	<input type="checkbox"/> AF - B5 Flange/Solid Shaft
<input type="checkbox"/> L - B14 Face Flange/ Double Solid Shaft	<input type="checkbox"/> AX - Tapped Feet/B14 Face Flange/Hollow Shaft
<input type="checkbox"/> VX - Tapped Feet/B14 Face Flange/Solid Shaft	<input type="checkbox"/> AXF - Tapped Feet/B5 Flange/Hollow Shaft
<input type="checkbox"/> VXF - Tapped Feet/B5 Flange/Solid Shaft	
<input type="checkbox"/> LX - Tapped Feet/B14 Face Flange/Double Solid Shaft	

③ Shaft/Mounting Options	
<input type="checkbox"/> Keyed Hollow Shaft	<input type="checkbox"/> D - Torque Arm
<input type="checkbox"/> SH - Shrink Disc & Cover	<input type="checkbox"/> SM -Stainless Steel Shaft
<input type="checkbox"/> MH - GRIPMAXX™	<input type="checkbox"/> SWV -Special Solid Shaft
<input type="checkbox"/> H - Hollow Shaft Cover	<input type="checkbox"/> SWA -Special Hollow Shaft
<input type="checkbox"/> B - Fixing Element Kit	<input type="checkbox"/> Worm Footplate Kit

④ Reducer Options	
<input type="checkbox"/> OSG - Oil Sight Glass	<input type="checkbox"/> LL - Long Term Storage
<input type="checkbox"/> MDP - Magnetic Drain Plug	<input type="checkbox"/> PR - Flange Pilot Removal
<input type="checkbox"/> ADP - Additional Drain Plug	<input type="checkbox"/> VI - Flouro-rubber Seals

⑤ Input Shaft	NEMA Adapter	IEC	Integral Motors	Integral Premium Efficient Motors	Integral Intermittent Duty (60 min) Motors
W	N56C	IEC 63	63S/4 - 0.16hp	80LP/4 - 1hp	80L/4 - 1hp
	N140TC	IEC 71	63L/4 - 0.25hp	90SP/4 - 1.5hp	90S/4 - 1.5hp
	N180TC	IEC 80	71S/4 - 0.33hp	90LP/4 - 2hp	90L/4 - 2hp
	N210TC	IEC 90	71L/4 - 0.50hp	100LP/4 - 3hp	100L/4 - 3hp
	N250TC	IEC 100	80S/4 - 0.75hp	112MP/4 - 5hp	100LA/4 - 5hp
		IEC 112		132SP/4 - 7.5hp	112M/4 - 5.4hp
		IEC 132		132MP/4 - 10hp	132S/4 - 7.5hp
		IEC 160			132M/4 - 10hp
				Other Speeds Available	Other Speeds Available

Product Specifications

Ratio :1

— OR —

Output Speed rpm

Mounting Position

M1

M2


M3

M4

M5

M6

Special



Paint

Standard Stainless Steel Paint

NSD+ (gray)

NSD+W (white)

NSD-X3 (gray)

NSD-X3W (white)

NSD-Tuph

Special

Lubricant

Standard

Synthetic

Food Grade

Other

Solid Shaft Side (if required)

Shaft Side A

Shaft Side B

Shaft Side A&B

Hollow Shaft Diameter (if required)

B5 Flange Side (if required)

Flange Side A

Flange Side B

Flange Side A&B

B5 Flange Diameter (if required)

Torque Arm Side & Location (if required)

Side A

Side B

Location

Shrink Disc /GRIPMAXX™ Side (if required)

Side A

Side B

H66 Side (if required)

H66 Side A

H66 Side B

Gearmotor Only Details

Voltage & Frequency

230/460V-60Hz (460V only ≥ 40 hp)

575V-60Hz

208V-60Hz

400V-50Hz

115/230V-60Hz, 1 ph.

Other


Terminal Box Pos.

TB1

TB2

TB3

TB4



Mtg. Pos. M1 Shown


Conduit Entry Loc.

CE I *

CE II

CE III *

CE IV



Mtg. Pos. M1 Shown

* Brakemotor