

	Gear Unit	Shaft/Mounting	Reducer Options	-	Input/Motor	Motor Options
SK	1	2	3	-	4	

1	Gear Unit	2	Shaft/Mounting																			
	<table border="1"> <tr><td>072.1</td><td></td></tr> <tr><td>172.1</td><td></td></tr> <tr><td>372.1</td><td>373.1</td></tr> <tr><td>572.1</td><td>573.1</td></tr> <tr><td>672.1</td><td>673.1</td></tr> <tr><td>772.1</td><td>773.1</td></tr> <tr><td>872.1</td><td>873.1</td></tr> <tr><td>972.1</td><td>973.1</td></tr> </table>	072.1		172.1		372.1	373.1	572.1	573.1	672.1	673.1	772.1	773.1	872.1	873.1	972.1	973.1		<input type="checkbox"/> - Footed <input type="checkbox"/> F - B5 Flange • B5 Flange Diameter <input style="width: 100px;" type="text"/>		<input type="checkbox"/> Z - B14 Flange <input type="checkbox"/> XZ - Foot/B14 Flange <input type="checkbox"/> XF - Foot/B5 Flange • XF Flange Diameter <input style="width: 100px;" type="text"/>	
072.1																						
172.1																						
372.1	373.1																					
572.1	573.1																					
672.1	673.1																					
772.1	773.1																					
872.1	873.1																					
972.1	973.1																					
		3	Reducer Options																			
			<input type="checkbox"/> VL - Heavy Duty Output Bearings <input type="checkbox"/> AL - Axial/Thrust Output Bearings <input type="checkbox"/> PR - Flange Pilot Removal <input type="checkbox"/> VI - Fluoro Rubber Seals <input type="checkbox"/> SWV - Special Solid Shaft <input type="checkbox"/> SM5 - Stainless Steel Output Shaft		<input type="checkbox"/> OSG - Oil Sight Glass <input type="checkbox"/> OA - Oil Expansion Chamber <input type="checkbox"/> LL - Long Term Storage <input type="checkbox"/> MDP - Magnetic Drain Plug <input type="checkbox"/> ADP - Additional Drain Plug																	

4	Input Shaft	NEMA Adapter	IEC	Integral Motors		Integral Energy Efficient Motors	
	W	N56C N140TC N180TC N210TC N250TC N280TC N320TC	IEC 63 IEC 71 IEC 80 IEC 90 IEC 100 IEC 112 IEC 132 IEC 160 IEC 180 IEC 200	63S/4 - 0.16hp 63L/4 - 0.25hp 71S/4 - 0.33hp 71L/4 - 0.50hp 80S/4 - 0.75hp 80L/4 - 1hp 90S/4 - 1.5hp 90L/4 - 2hp 100L/4 - 3hp 100LA/4 - 5hp	112M/4 - 5.4hp 132S/4 - 7.5hp 132M/4 - 10hp 160M/4 - 15hp 160L/4 - 20hp 180MX/4 - 25hp 180LX/4 - 30hp 200L/4 - 40hp 225S/4 - 50hp	80LH/4 - 1hp 90SH/4 - 1.5hp 90LH/4 - 2hp 100LH/4 - 3hp 112MH/4 - 5hp 132SH/4 - 7.5hp 132MH/4 - 10hp	160MH/4 - 15hp 160LH/4 - 20hp 180MH/4 - 25hp 180LH/4 - 30hp 200LH/4 - 40hp 225SH/4 - 50hp
				Other Speeds Available		Other Speeds Available	

Product Specifications

Ratio <input style="width: 100px;" type="text"/> :1 — OR — Output Speed <input style="width: 100px;" type="text"/> rpm	Mounting Position <input type="radio"/> M1 <input type="radio"/> M2 <input type="radio"/> M3 <input type="radio"/> M4 <input type="radio"/> M5 <input type="radio"/> M6 <input type="radio"/> Special _____		Paint <input type="radio"/> No Paint (Standard) <input type="radio"/> Stainless Steel Paint <input type="radio"/> NSD+ (gray) <input type="radio"/> NSD+W (white) <input type="radio"/> NSD-X3 (gray) <input type="radio"/> NSD-X3W (white) <input type="radio"/> Special _____	Lubricant <input type="radio"/> Standard <input type="radio"/> Synthetic <input type="radio"/> Food Grade <input type="radio"/> Other _____
--	---	--	---	--

Shaft Diameter


Gearmotor Only Details

Voltage & Frequency

- 230/460V-60Hz
- 575V-60Hz
- 208V-60Hz
- 400V-50Hz
- 115/230V-60Hz, 1 ph.
- Other _____

Terminal Box Pos.

- TB1
- TB2
- TB3
- TB4




Mtg. Pos. M1 Shown

Conduit Entry Loc.

- CE I *
- CE II
- CE III *
- CE IV

* Brakemotor



Mtg. Pos. M1 Shown